



MUNICIPAL SERVICES DEPARTMENT
ENGINEERING DIVISION
156 S. BROADWAY, SUITE 150
TURLOCK, CA 95380

PHONE: (209) 668-5520
FAX: (209) 668-5563
TDD: (800) 735-2929
engineering@turlock.ca.us

Date: 11/18/25

City Project No.: 25-051

Addendum No.: 2

Plan holders:

The City has received several requests for information and has provided clarification below.

- 1. Question:** Is striping repair after the trench is patched part of the scope for the above mentioned project?

Answer: No.

Item No. 1 – The “Final Pavement Report” prepared by Crawford & Associates, Inc., pothole information from Roads Program CIP Project No. 23-067 are provided for reference only. The Contractor is responsible for verifying all existing conditions, pavement sections, and quantities in the field. These documents are available in the “Supplemental Material” at <https://www.cityofturlock.org/capitalprojects>

Item No. 2 – The typical section designed for El Paseo St. from the Roads Program CIP Project No. 23-067 Design Plans are provided below for reference only.

Revisions to Plans and Specifications

The following additions, deletions or modifications shall become part of the Contract Documents:

Strikethrough text (~~text~~) indicates deletions.

Bold Italicized text (**text**) indicates additions.

Project Specifications:

Item No. 3 - Section 10.12 is amended to read as follows:

10.12 SANITARY SEWER SERVICE LATERAL (SDR-26) WITH CLEAN OUT:

Contractor shall replace sanitary sewer service laterals ~~using a trenchless installation method~~ in accordance with the City of Turlock Standard Specifications and Drawings, the Project Plans, and these Special Provisions. Pipe material shall be PVC SDR-26.

~~The trenchless method shall be performed in a manner that minimizes disturbance to existing pavement, landscaping, and other surface improvements. Prior to installation, the Contractor shall verify the horizontal and vertical alignment of the existing service connection and confirm the location of at the property line clean-out and new mainline connection. All disturbed areas, including paving, concrete, and landscaping, shall be restored to their original condition or better, at no additional cost to the City.~~ **Existing curb and gutter**

shall not be disturbed for this work. Hand digging will be required within six (6) inches of existing curb and gutter. The Contractor shall ensure that compaction activities do not disturb or undermine existing curb and gutter. All compaction testing under existing curb and gutter shall be done in the presence of a City Inspector. All other disturbed areas such as landscaping shall be restored to their original condition or better.

Contractor shall pothole the locations of all sanitary sewer services to be replaced and confirm elevations will work to connect to **the new** sewer main. Provide pothole information to the City within five (5) working days prior to starting any excavation and notify the City of any conflicts. Contractor shall dig, lay, and backfill sanitary sewer pipe in accordance with City of Turlock Standard Specifications Section 14 (Errata 1), the Project Plans, and these Special Provisions.

PAYMENT

The contract price paid per each for Sanitary Sewer Service Lateral **with Clean Out (SDR-26)** shall include full compensation for furnishing all labor, materials, tools, equipment, and incidentals and for doing all the work involved in **laying and** constructing the sanitary sewer pipe **lateral with clean out, including all trenching and backfill per City Standard Drawings T-1 and T-2 (trench repair steps 1 and 2),** complete in place, as shown on the Project Plans, and as required by law, as specified in the City of Turlock Standard Specifications and these Special Provisions, and as directed by the City Engineer. Specifically included in the price paid for each Sanitary Sewer Service Lateral is the cleanout assembly and all materials required to connect to existing sewer main **per City of Turlock Standard Specifications and Drawings.**

Item No. 4 - Section 10.13 is amended to read as follows:

10.13 SANITARY SEWER SERVICE LATERAL (C-900 DR-14) WITH CLEAN OUT:

Where sanitary sewer service laterals cross within 12-in of a water main, a minimum 20-ft section of the sanitary sewer service shall be PVC C900-07, Pressure Class 305, DR-14 centered on the water main. Contractor shall replace sanitary sewer service laterals ~~using a trenchless installation method~~ in accordance with the City of Turlock Standard Specifications and Drawings, the Project Plans, and these Special Provisions.

~~The trenchless method shall be performed in a manner that minimizes disturbance to existing pavement, landscaping, and other surface improvements.~~ Prior to installation, the Contractor shall verify the horizontal and vertical alignment of the existing service connection ~~and confirm the location of~~ **at** the property line cleanout and mainline connection. **Existing curb and gutter shall not be disturbed for this work. Hand digging will be required within six (6) inches of existing curb and gutter. The Contractor shall ensure that compaction activities do not disturb or undermine existing curb and gutter. All compaction testing under existing curb and gutter shall be done in the presence of a City Inspector. All other disturbed areas such as landscaping shall be restored to their original condition or better.** All disturbed areas, including paving, concrete, and landscaping, shall be restored to their original condition or better, at no additional cost to the City.

Contractor shall pothole the locations of all sanitary sewer services to be replaced and confirm elevations will work to connect to **the new** sewer main. Provide pothole information to the City within five (5) working days prior to starting any excavation and notify the City of any conflicts. Contractor shall dig, lay, and backfill sanitary sewer pipe in accordance with City of Turlock Standard Specifications Section 14 (Errata 1), the Project Plans, and these Special Provisions.

PAYMENT

The contract price paid per each for Sanitary Sewer Service Lateral (C-900 DR-14) **with clean-out** shall include full compensation for furnishing all labor, materials, tools, equipment, and incidentals and for doing all the work involved in constructing the sanitary sewer pipe **lateral with clean out, including all trenching and backfill per City Standard Drawings T-1 and T-2 (trench repair steps 1 and 2)**, complete in place, as shown on the Project Plans, and as required by law, as specified in the City of Turlock Standard Specifications and these Special Provisions, and as directed by the City Engineer. Specifically included in the price paid for each Sanitary Sewer Service Lateral (C-900 DR-14) is the cleanout assembly and all materials required to connect to existing sewer main **per City of Turlock Standard Specifications and Drawings.**

Sincerely,



Janine Lee
Project Manager